

# TAPECONCURRENT

## Technical data sheet

### 4303 – 4305 PVC Insulating Tape

#### **Dimensions:**

Thickness 0.15 mm  
Roll widths from 15 to 100 mm

#### **Specifications:**

Backing	Soft PVC
Adhesive	Solvent Rubber
Tensile Strength	20 N/cm
Elongation	180%
Peel Adhesion	1,5N/cm
Voltage Breakdown	7.0 KV

Standard Colours 4304 Black,4303 grey,4305 white,4309 red, 4307 Yellow, 4306 Blue,4308 Green and Yellow/Green  
Other colours on request

#### **Application:**

A 0.15mm PVC insulating tape with a pressure sensitive rubber adhesive. Tape is flame-retardant and is used as a general purpose insulating and electrical tape.

Suitable for wrapping and marking of electric wires and cables. Also used for automotive wrapping, colour coding etc.

#### **Storage**

Storage should be in dry, well ventilated rooms with a temperature around 20°C. Products should be protected from continuous exposure to direct sunlight. Always apply the product on clean and dry surfaces.

*All statements, technical information and recommendations herein are based on tests we believe to be reliable, but the accuracy and completeness thereof is not guaranteed and the following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, User shall determine the suitability of the product for its intended use, and User assumes all risk and liability whatsoever in connection therewith. Seller reserves the right to improve the product and accordingly change the specification without notice. Neither Seller nor Manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of or Seller and Manufacturer.*