

TAPECONCURRENT

Technical data sheet

8409 Transfer tape

reverse wound version for ATS/ATG dispenser

TECHNICAL DETAILS	VALUE
Adhesive:	modified acrylic Reinforced with glass fibres
Thickness:	50 μ (+/- 10%)
Peel adhesion on steel after 1 minute:	6,25 N/ 25mm
Temperature resistance:	-30 to 110 $^{\circ}$ c

STORAGE DETAILS

The conditions under which this product is stored affect its performance. Storage should be in dry, well ventilated rooms with a reasonable consistent temperature around 20 $^{\circ}$ c and protected from continuous exposure to direct sunlight. The product should always be applied to clean, dry surfaces.

The information supplied is accurate to our best knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such a advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer.