

TAPECONCURRENT

Product datasheet 8728

DESCRIPTION:

Heavy-duty polyester double-sided tape with high coating weight.

A double-sided tape with a synthetic rubber adhesive, a strong, heat-resistant polyester carrier and a brown siliconized paper liner. The double sided polyester tape has an excellent adhesive and filling power to low energy, smooth and rough surfaces due to the very high coating weight. On top of that the tape features a high shear.

APPLICATION:

Permanent fixing of carpet, carpet tiles, plinths, profiles, ceiling strips and decoration film.

CHARACTERISTICS:

Carrier:	Polyester
Liner:	Siliconized paper 70µm
Adhesive:	Synthetic rubber
Total thickness, without liner (µm)	115
Adhesion to steel at RT (N/25mm)	25
Rolling ball at RT (cm)	< 1
Shear resistance at RT (hours)	> 168
Temperature range (°C)	-10 to +75

AVAILABLE SIZES:

Width (mm)	Upon request
Length (M)	Upon request
Core (mm)	3"

CONDITIONS:

Store in a cool dry place away from sunlight and direct heat sources.

As far as the storage conditions are respected, the product is guaranteed 12 months.

DISCLAIMER:

All statements, technical information and product recommendations are based on tests in our laboratories we believe to be reliable. In all cases the user should however determine the suitability of the product for his intended use and user assumes all risk and liability whatsoever in connection therewith. Neither seller or manufacturer shall be reliable for any loss or damage – direct, incidental or consequential – arising from the use of the product. Details of test methods are available on request.