

# TAPECONCURRENT

## TAPE OP MAAT

### Technical datasheet

## 1310 - 1312

### PP acrylic packaging tape

#### Product description

This tape consists of a biaxially stretched clear, tearproof PP-film, of which one side is coated with a water-based acrylic glue.

- ✓ Very clear transparency
- ✓ Suited for long-term applications
- ✓ Ageing and UV-stable

#### Application

This PP acrylic packaging tape is applied whenever ageing- and UV-stability are of importance. Because of the special glue, this tape must be pressed carefully when being processed. Resistant acrylic glues are especially suited for long-term sticking.

#### Technical data

Technical Property	Value	Margins
Foil thickness	0,025 mm	+/- 10%
Total thickness	0,043 mm	+/- 5%
Tensile strength	80 N / 25 mm	+/- 10%
Adhesion to steel	5,5 N / 25 mm	+/- 10%
Elongation at break	170%	+/- 10%
Temperature resistance	Up to +60°C	

#### Sizing

##### **Available widths**

12 mm, 15 mm, 19 mm, 25 mm, 38 mm, 48 mm, 50 mm, 75 mm

##### **Available lengths**

30 m, 50 m, 66 m, 100 m, 132 m

#### **Colours**

Brown, clear, white

#### **DISCLAIMER**

The above-mentioned details are based on averages of all information without guarantee. All users are obliged to examine the usability of the product of their specific requirements.