

TAPECONCURRENT

TAPE OP MAAT

Technical datasheet

2613

Paper carton sealing tape

Product Description

Paper carton sealing tape for packaging with a 58 g/m² saturated crepe paper, brown, with a natural rubber and resins based adhesive.

Natural rubber and resins based adhesive:

- ✓ good adhesion even on different types of cardboard
- ✓ good adhesion even if stored in cold temperature after closing

Saturated paper backing:

- ✓ Resistant to box shock
- ✓ Hand tearable
- ✓ Identifies pilferage (as damaged cartons would be recognized if resealing were attempted)

Product application

Paper carton sealing tape for standard packaging. Printable (not in negative) or available printed up to 3 colours (30% max printable surface). Tape must be applied at room temperature.

Characteristics

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	58 g/m ² saturated crepe paper; brown
Adhesive	natural rubber and resins based
Adhesion to Steel	3,3 N/25mm
Tensile Strength MD	85 N/25mm
Elongation at break	7%
Total Thickness	0,12mm
Temperature Resistance	60°C

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Printed rolls with length more than 50 meters: 3months of shelf life.

Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of our knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.