

TAPECONCURRENT

TAPE OP MAAT

Technical datasheet

2649

Fiberglass reinforced paper tape

Product description

Fiberglass reinforced paper tape for secure (heavy duty) packaging.

- ✓ Suitable for heavy duty packaging
- ✓ Specially designed to be used for e-commerce
- ✓ Extreme adhesion power to all surfaces, including recycled cardboard
- ✓ 100% PEFC certified adhesive tape, paper made of certified sustainable sources
- ✓ The tape functions as a temper evident seal, protecting the packaging content
- ✓ Suitable either for manual application or automated packaging systems
- ✓ Easy to apply with conventional manual tape dispensers anywhere and on any surface

Product storage

Tape performance is guaranteed within the first 6 months. Product must be kept in its original packaging and in a dry atmosphere away from direct sunlight. For product traceability, the production batch number on the box of the product has to be indicated

Characteristics

Physical and performance characteristics shown below are obtained following tests recommended by AFERA and manufacturer. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

Adhesive	Synthetic rubber (hotmelt)
Backing	Fiberglass reinforced 100% PEFC certified paper
Backing thickness	200µm
Total thickness	240µm
Peel Adhesion	> 16 N/cm
Tensile Strength	115 N/cm
Elongation at break	6%
Service Temperature	-10°C / +60°C

Safety

Product does not contain any dangerous or unhealthy components. Safety data sheets are available based on directive 91/155/EC. This tape complies with European 2004/12/CE Packaging directive.