

TAPECONCURRENT

TAPE OP MAAT

Technical datasheet

5434WI

**PE Acrylic, PET reinforced, high performance
sealing and bonding tape**

Product Description

Single sided tape

Adhesive

The adhesive on this product is modified acrylic. It shows high adhesion strength and very high tack combined with superior ageing and weatherability performance. The adhesion to a very wide range of surfaces is excellent, including low energy substrates (e.g. PE, PP and non-woven materials).

Product structure

Support	PES/PVA-scrim, PE-foil 60µm (diff. colours and prints)
Interliner	Release paper, yellow, 90 g/m ²
Adhesive weight	240 g/m ²
Total thickness	0,30 mm

Characteristics

Temperature resistance	from -40 °C to +80 °C
<i>(According to internal test method AA-B-12-07)</i>	
Adhesive strength	min 35 N/25 mm
<i>(According to AFERA 5001)</i>	Contact time: 1 h

Note

All our products are subjected to a strict quality control by our QM-System, which is in accordance with ISO/TS 16949, DIN EN ISO 9001 and DIN EN ISO 14001. The information is based on our present knowledge and our experience. Because of the large number of possible influences during the processing and application of our products, this information does not release the user from the obligation to conduct his own tests and trials. Users of our products are responsible for observing any patent rights that may exist and for following existing regulations. Our applications technology section is always pleased to give advice about suitability tests on original materials.