

TAPECONCURRENT

PP Acrylic Packaging tape 1310 - 1312

Article description:

This tape consists of a biaxially stretched, clear, tearproof, PP-film of which one side is coated with a water-based acrylic glue.

| | |
|--------------------------|--|
| <u>available widths:</u> | 12 – 15 - 19 – 25 – 38 – 48 – 50 – 75 mm |
| <u>roll length:</u> | 30 – 50 – 66 – 100 – 132 m |
| <u>colour:</u> | brown, clear and white |

Product data

| | | |
|-------------------------|---------------|------------|
| foil-thickness: | 0,025 mm | (+/- 10 %) |
| total-thickness: | 0,043 mm | (+/- 5 %) |
| tensile strength: | 80 N/25 mm | (+/- 10 %) |
| adhesion to steel: | 5,5 N/25 mm | (+/- 10 %) |
| elongation at break: | 170 % | (+/- 10 %) |
| temperature resistance: | up to + 60° C | |

Use:

The Packfilm 801 is employed whenever ageing- and UV-stability are of importance. Because of the special glue this tape has to be pressed carefully when being processed. Resistant acrylic glues are especially suited for long-term stickings.

The above mentioned details are based on averages of all information without guarantee. All user are obliged to examine the usability of the product of their specific requirements.