

TAPECONCURRENT

Technical Datasheet

3013 – 3019 Duct tape universeel

DESCRIPTION:

Polyester cloth / polyethylene film with an aggressive natural rubber pressure sensitive adhesive combine to provide a quality utility product. Conformable to irregular surfaces.

COMMON APPLICATIONS:

Packaging, wrapping & sealing, binding & bundling, and general maintenance.

PHYSICAL PROPERTIES:

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing:	2.0 mil PE film
Reinforcement:	PET cloth
Adhesive:	Natural Rubber / resin
Total Thickness:	0.178mm
Adhesion to steel:	11.0N / 25mm
Quick stick to steel:	3.7N / 25mm
Elongation:	15.0% (at break)
Tensile strength:	74N / 25mm

STORAGE CONDITIONS:

Product should be stored in a cool, dry area in original packaging, and used within 12 months of shipment date.

The information supplied is accurate to our best knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assesment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such a advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer.