

TAPECONCURRENT

Technical Datasheet

3031 – 3033 – 3034

DESCRIPTION:

High quality professional duct tape with unique adhesive power.

A synthetic rubber based duct tape with a waterproof PE coated fabric which is tearable by hand. A strong initial tack, an extremely high adhesive power and a very high shear adhesion.

COMMON APPLICATIONS:

Due to the excellent adhesive characteristics and high shear, this tape is perfectly suitable for professional applications on smooth and rough surfaces such as stone, concrete, wood and plastics and for hanging products onto walls.

PHYSICAL PROPERTIES:

The following data are nominal values. The data should not be considered as specifications.

Backing:	PE film
Reinforcement:	fabric
Adhesive:	synthetic rubber
Total Thickness:	0.220 mm
Mesh density (fabric)	26
Adhesion to steel:	28 N / 25mm
Rolling ball tack:	<3cm
Tensile strength:	105N / 25mm
Service temperature:	-10 up to 75°C

STORAGE CONDITIONS:

Store in a cool dry place away from sunlight and direct heat sources.

As far as the storage conditions are respected, the product is guaranteed 12 months.

The information supplied is accurate to our best knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such a advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer. All statements, technical information and product recommendations are based on tests in laboratories we believe to be reliable. In all cases the user should however determine the suitability of the product for his intended use and user assumes all risk and liability whatsoever in connection therewith. Neither seller or manufacturer shall be liable for any loss or damage - direct, incidental or consequential - arising from the use of the product.