

# TAPECONCURRENT

## Technical Datasheet 4210 - 4219

<b>DESCRIPTION</b>	Silent tape single sided self-adhesive tape
<b>BACKING</b>	PVC Film 32 my $\pm$ 8%
<b>ADHESIVE DESCRIPTION</b>	Natural rubber, hydrocarbonic resins, solvent based, antioxidants, colouring agents.
<b>TOTAL THICKNESS</b>	52 my $\pm$ 10%
<b>ADHESION TO STEEL</b>	1,9 N/cm $\pm$ 10%
<b>TENSILE STRENGTH</b>	48 N/cm $\pm$ 10%
<b>ELONGATION</b>	90% $\pm$ 20%
<b>TEMPERATURE RESISTANCE</b>	0 > < 70°C
<b>ROLLING BALL TACK</b>	$\leq$ 4 cm

### Application

Single sided carton saling tape, constant over time, with high resistance, softness and plasticity so as to adhere to any surface, from industrial packaging (standard and most recycled cartons) to paper mills.

<b>Natural rubber adhesive:</b>	<ul style="list-style-type: none"><li>• Performing even at low temperature.</li><li>• Good adhesion in several application.</li><li>• Suitable for use on most recycled cartons.</li></ul>
<b>PVC backing:</b>	<ul style="list-style-type: none"><li>• Well adaptable to different shapes.</li><li>• Good elongation.</li><li>• No noise unwinding.</li></ul>

This information is gained from sample tests conducted on a material similar to that produced and purchased within the six months preceding the date of order's completion. These data therefore indicate a reference average value to the specifications established by Autoadesivi Magri.

Appearance and technical features are subject to variations over time caused by ageing, anyway they do not affect the product's quality and functionality.