

TAPECONCURRENT

Technical data sheet

8756 Double Sided PP Exhibition Tape

DESCRIPTION

Removable double sided adhesive tape.

Backing	0.050 mm OPP; yellow
Adhesive	Outer side: acrylic – Inner synthetic rubber resins
Liner	Double sided siliconized paper; white

	Unit	Value	Method
Total thickness (without Liner)	mm	0.150	PSTC 133
Adhesion to steel	N/25mm	Int: 37 – Ext: 3.7	PSTC 101
Tensile strength MD	N/25mm	50	PSTC 131
Elongation at break	%	600	PSTC 131
Temp. Resistance	C°	60°C	=

APPLICATION

Floor removable double sided tape, recommended for holding exhibitions, and promotion, events, temporary applications in household use when carpets, runners, etc, floor holding are required.

The removable side of the tape is the outer: first apply the tape to the floor, then remove the liner and apply the carpet.

Please always test on any surface involved. After application removal is suggested within 15 days.

Features	Benefits
Synthetic rubber and resins (<i>inner side</i>)	✓ High adhesion on all carpets, runners, etc. ✓ Safe holding
Acrylic adhesive (<i>outer side</i>)	✓ Easily removable without adhesive transfer ✓ High performance on several surfaces
OPP backing	✓ High conformable ✓ Hand tearable ✓ Position highlight thanks to the yellow colour ✓ Removable without breaking

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use.

Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

All statements, technical information and recommendations herein are based on tests we believe to be reliable, but the accuracy and completeness thereof is not guaranteed and the following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, User shall determine the suitability of the product for its intended use, and User assumes all risk and liability whatsoever in connection therewith. Seller reserves the right to improve the product and accordingly change the specification without notice. Neither Seller nor Manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of or Seller and Manufacturer.