

## tesa® 4306

### Premium Painters tape for indoor painting applications

The very name of tesa® 4306 painters tape makes its standard quite clear and its outstanding adhesion results in sharp paint and varnish edges. This high-quality paper masking tape makes both clean and convenient painting work possible, because the extremely flat but high tear-resistant paper backing and simple unrolling make it extremely easy to use. In addition, this premium painters tape helps you avoid time-consuming and expensive touching-up work. As a professional aid, the innovative paper masking tape is a reliable partner for painting work of all kinds.

### Main Application

The tesa® 4306 painters tape comprises a special paper backing, which is supple, tear-proof and flat for extremely clean and sharp paint edges, and it's coated with a modern, solvent-free adhesive compound which guarantees especially balanced adhesive strength. tesa® 4306 is usable for all indoor painting applications for up to 14 days as well as for outdoor applications up to 3 days.

- Suitable for all kind of painting and masking applications
- Indoor masking (up to 14 days)
- Outdoor masking (up to 3 days)
- Masking for straight line and slight curves

### Technical Data

▪ Backing material	slightly-creped paper	▪ Elongation at break	7 %
▪ Total thickness	95 µm	▪ Tensile strength	37 N/cm
▪ Type of adhesive	natural rubber	▪ UV-resistance	0.5 weeks
▪ Adhesion to steel	2 N/cm		

### Properties

▪ Hand tearability	● ● ● ●	▪ Sharp colour edge	● ● ● ●
▪ Suitable for rough surfaces	● ● ●	▪ Conformability	● ● ●
▪ Paint anchorage	● ● ● ●		

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

### Additional Information

The natural rubber adhesive is generally not UV resistant. tesa® 4306 should therefore not be used for more than 3 days outdoors.

For latest information on this product please visit <http://l.tesa.com/?ip=04306>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.