

# tesa® 60422 PV0

### **Product Information**

Heavy duty carton sealing tape

tesa® 60422 is a premium packaging tape based on a very strong PVC backing and a natural rubber adhesive. Even heavy boxes or boxes with multiflute cardboard with high flap tension can be closed safely. The tensile strength and elongation characteristics of the backing make the product resistant to high shock impacts.

#### Features

- Good adhesion even in recycled cartons
- Excellent tack and long-lasting adhesion
- Silent unwinding
- Ideal for storage in extreme temperature conditions and high moisture

### Main Application

- Carton sealing of very heavy cartons or boxes with hazardous content
- Packaging, bundling and closing
- Brand showcase and advertisement purposed (printability)

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Technical Data**

<ul><li>Backing material</li><li>Total thickness</li><li>Type of adhesive</li></ul>	PVC film 88 μm natural rubber	<ul><li>Elongation at break</li><li>Tensile strength</li></ul>	100 % 72 N/cm
Adhesion to			
• steel	2.0 N/cm		
<ul><li>Properties</li><li>Automatic application</li><li>Manual application</li></ul>	yes yes	<ul><li>Printability</li><li>Low noise unwinding</li></ul>	yes
Evaluation across relevant tesa <sup>®</sup> assortment: •••• very good ••• good •• medium • low			
Additional Information tesa® 60422 is easily printable.	-		
Available colours: havana/chamois.			



## tesa® 60422 PV0

**Product Information** 

#### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit http://l.tesa.com/?ip=60422