

tesa® 7475 PV2

tesa® 7475 has been successfully deployed for many years, both when it comes to assessing the release properties of silicone coatings (FINAT 10 or similar) and testing the curing of silicone coatings (FINAT 11 or similar).

For a comprehensive characterization of release properties it is recommended to use both tesa® 7475 (acrylic adhesive) and tesa® 7476 (natural rubber adhesive).

It is recommended to store tesa® 7475 at 23 °C and 50 % relative humidity.

Main Application

Characterization of silicone coatings

Technical Data

▪ Backing material	PET	▪ Type of liner	glassine
▪ Type of adhesive	acrylic	▪ Shelf life time	24 months

For latest information on this product please visit <http://l.tesa.com/?ip=07475>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.