

TAPECONCURRENT

Product Data sheet Masking Tape 2231A

Masking tape for automotive repair workshops

Backing:	59 g/m ² yellow saturated crepe paper
Adhesive:	Dry natural rubber and resins solvent based
Total thickness	0.130 mm
Adhesion to steel	5 N/25mm
Tensile strength MD	90 N/25mm
Elongation at break	8 %
Temp. Resistance	110 °C (30 min), suitable for 80°C oven drying

Application

Masking tape suitable for applications requiring high temperature resistance

Features

Dry natural rubber and resins solvent based adhesive

Saturated paper backing

Benefits

- Good adhesion even on irregular surfaces
- High performance even in overlapping and with masking paper applied
- Heat resistant up to 110°C (30 minutes)
- Usable even for refinishing with Infra Red lamps
- Resistant to paint and lacquer
- Easy removal without adhesive residue

- The yellow colour allows even shading, creating clear contrast with most frequent colours
- Well adaptable to most shapes
- Compatible with most common paints and lacquers
- Hand tearable

Product shelf life and storage: 12 months, based on the product being stored at 23°C/50% relative humidity out of direct sunlight.

Disclaimer:

All statements, technical information and product recommendations are based on tests in our laboratories we believe to be reliable. In all cases the user should however determine the suitability of the product for his intended use and user assumes all risk and liability whatsoever in connection therewith. Neither seller or manufacturer shall be reliable for any loss or damage – direct, incidental or consequential – arising from the use of the product. Details of test methods are available on request.