

# TAPECONCURRENT

## Technical data sheet

### 5411 PE all weather tape

**Carrier:**

Polyethylene film

**Adhesive:**

Acrylic

**Applications:**

Surface protection, Masking, Packaging.

**Technical description:**

Elongation at break  
Tensile strength  
Peel adhesion to steel  
Rolling ball tack  
Thickness carrier  
Total thickness  
Outdoor UV resistance

**Technical values:**

180%  
9 N/cm  
3.0 N/cm  
≤10 cm  
120μ ± 10%  
160μ ± 10%  
9 months in Northern Italy

When stored in the original packaging at 21°C and at 50% relative humidity the product has a shelf life of 12 months. Prior to use carefully check that the contact surfaces are totally dry and clean from oil, grease and dust.

Test methods: AFERA, PSTC, IEC EN 60454-2

*All statements, technical information and recommendations herein are based on tests we believe to be reliable, but the accuracy and completeness thereof is not guaranteed and the following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, User shall determine the suitability of the product for its intended use, and User assumes all risk and liability whatsoever in connection therewith. Seller reserves the right to improve the product and accordingly change the specification without notice. Neither Seller nor Manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of or Seller and Manufacturer.*