

TAPECONCURRENT

Technical data sheet

8313 Double sided tissue tape, high tack

Product description:

A double sided tissue tape with a very high tack modified Solvent Acrylic adhesive. Hand tearable, with a white moisture stable polycoated liner and excellent ultraviolet and plasticiser resistance. Used for a wide variety of purposes, differing from splicing all kinds of paper and plastics as well as the lamination of foam- and rubber-materials. Good durability on low-energy surfaces

TECHNICAL DETAILS

TYPICAL VALUE

Thickness carrier:	0,03 mm
Thickness adhesive + carrier:	0,13 mm
Adhesive:	solvent acrylic
Liner:	90 grams
Adhesion to steel:	0.6 kg/cm
Temperature resistance: (term)	-25 to 150°C (short
Tensile strength:	0.71 kg/cm
Elongation:	2%

All statements, technical information and recommendations herein are based on tests we believe to be reliable, but the accuracy and completeness thereof is not guaranteed and the following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, User shall determine the suitability of the product for its intended use, and User assumes all risk and liability whatsoever in connection therewith. Seller reserves the right to improve the product and accordingly change the specification without notice. Neither Seller or Manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of or Seller and Manufacturer.