

# tesa® Professional 4612



## Product Information

### Waterproof fabric repair tape

tesa® 4612 is a fabric repair tape comprising a fabric substrate in combination with a natural rubber adhesive mass. The waterproof fabric repair tape is easy to handle, can be torn by hand and is suitable for a great number of DIY applications. Thanks to its superior adhesive strength, it also sticks to rough and dusty surfaces such as brickwork or wood. tesa® 4612 makes work easier for craftsmen and ensures outstanding work results as well as satisfied customers.

### Main Application

- Sealing of pipes and ducts
- Bonding of construction and protection films
- Closing of covering foils
- Application on brickwork and timber
- Fixing, closing, packaging and a lot more

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Technical Data

• Backing material	PE laminated cloth	• Tensile strength	30 N/cm
• Total thickness	230 µm	• Temperature resistance (30 min)	95 °C
• Type of adhesive	natural rubber	• Mesh	27 count per square inch
• Elongation at break	15 %		

#### Adhesion to

- steel 4.4 N/cm

#### Properties

- |                       |     |                       |    |
|-----------------------|-----|-----------------------|----|
| • Hand tearability    | ●●● | • Abrasion resistance | ●● |
| • Straight tear edges | ●●● | • Water resistance    | ●● |

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

# tesa® Professional 4612

## Product Information



### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=04612>