

TAPECONCURRENT

Product datasheet

4660 PVC Lane & Hazard Marking Tape

DESCRIPTION

Highly durable, flexible, plasticised PVC tape with a strong adhesive backing.

INSTRUCTIONS / USES

Used to mark aisles in warehouses, factories and hospitals etc. Also used to mark sports courts in halls & gymnasiums.

The striped versions are used to mark firefighting equipment & fire exits (Red & White); First aid equipment & safe areas (Green & White) or Low beams, steps, obstacles & general hazards (Black & Yellow)

For best results, apply in temperatures of not less than 5°C, ensuring that the surface is clean, dry and free from dust, grease oil etc. Unroll the tape applying even pressure to ensure a firm bond.

STANDARD VERSIONS

PLAIN COLOURS	STRIPED VERSIONS	ROLL SIZES
White, Black, Red, Green, Blue or Yellow	Red & White diagonals Green & White diagonals Black & Yellow diagonals Black & White diagonals	50mm wide x 33 Metres long <small>Other widths (25mm – 150mm) are available on request</small>

TECHNICAL INFORMATION

THICKNESS	TENSILE STRENGTH	ELONGATION AT BREAK
175µ	30 N/10mm	150%
ADHESIVE	APPLICATION TEMPERATURE	SERVICE TEMPERATURE
Rubber Resin	+5°C to + 40°C	0°C to + 60°C
COLOUR STABILITY	SHELF LIFE	STORAGE TEMPERATURE
UV resistant additive	12 months	+10°C to + 25°C