

tesa® 4154 Masking tape

tesa® 4154 is a filmic masking tape to be used to mask glass and metal during etching. tesa® 4154 withstands diluted acids and alkalis. To achieve sharp definition of colour edges tesa® 4154 is also used for multi-colour painting purposes.

Main Application

Masking tape for wide range of masking requirements

Technical Data

▪ Backing material	PVC film	▪ Adhesion to steel	3 N/cm
▪ Total thickness	65 µm	▪ Elongation at break	67 %
▪ Type of adhesive	natural rubber	▪ Tensile strength	60 N/cm

Properties

▪ Easy to remove	yes	▪ Printability	● ● ●
------------------	-----	----------------	-------

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04154>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.